

Hydraulischer Stellantrieb für Armaturen, Klappen und Ventile

NEU SA-H3



SPEZIFIKATIONEN

Betriebsdruck bis 210 bar

Drehmoment bis 250.000 Nm

Drehwinkel bis $90^\circ \pm 1$
(Sonderwinkel möglich)

Schutzart: IP65, IP67

Genau Positionierbarkeit

Umgebungstemperatur -10 bis 75°C

ISO 5211 Flansch

NEU

Doppelflansch

Winkelverstellung (feinjustierbar)

Gewicht reduziert

Steuerwelle nach VDI/VDE 3845 für
Standard-Näherungsschalter

Optional VDI/VDE 3845 Positionsabfrage

Diverse Steuerblöcke anschließbar
für Geschwindigkeitsregelung,
Rückschlagventil, u.v.m.



Hydraulic Part-Turn Actuator for Fittings, Flaps and Ball Valves

NEW SA-H3



SPECIFICATION

Working pressure up to 210 bar

Torque up to 250.000 Nm

Angle of rotation up to 90° ±1
(Special angle possible)

Protection class: IP65, IP67

Ability to position precisely

Temperature range -10 to 75°C

ISO 5211 flange

NEW

Double flange

Angular adjustment (fine adjustment)

Weight reduced

Camshaft according to VDI / VDE 3845
for standard proximity switch

Optional VDI / VDE 3845 position check

Various control blocks can be connected
for speed control, non-return valve and
many more

